

**Lexmark E220 Laser
Printer**

20S0101

Personal Printer - Professional

Tech Specs

Print Technology	Laser, Monochrome
<hr/>	
Print Resolution, Black	1200 Image Quality 300 x 300 dpi 600 x 600 dpi
<hr/>	
Print Speed (letter, black)	Up to 18 pages per minute
<hr/>	
Print Speed (A4, black)	Up to 17 pages per minute
<hr/>	
Time to First Page (black)	9.5 seconds
<hr/>	
Processor	100 MHz
<hr/>	
Memory base model, standard	8 MB
<hr/>	
Memory base model, maximum	72 MB
<hr/>	
Expandable Memory Options	Yes
<hr/>	
Apple Macintosh Operating Systems Supported	Apple Mac OS 8.6 - 9.x Apple Mac OS X
<hr/>	
Microsoft Windows 2000 (Professional/Server/Advanced Server) Microsoft Windows 95 4.00.950 or later	

Microsoft Windows Operating Systems Supported	Microsoft Windows 98, 2nd edition
	Microsoft Windows Me
	Microsoft Windows NT (4.00/4.00 Server)
	Microsoft Windows XP (Home, Professional)
	Microsoft Windows Server 2003 (Standard, Enterprise)

Linux Operating Systems Supported	Red Hat Linux 7.2, 7.3, 8.0, 9.0
	SuSE 7.3, 8.0, 8.1, 8.2 Linux

Other Operating Systems Supported	IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform
--	---

Citrix MetaFrame	Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
	Microsoft Windows NT 4.0 Terminal Server, with Citrix ^(R) MetaFrame ^(R) 1.8 or XP 1.0
	Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.

Paper Handling Configuration (Standard)	150-Sheet Input Tray
	Single Sheet Manual Feed Slot
	Single Sheet Exit
	100-Sheet Output Bin

Paper Handling Configuration (Optional)	250-Sheet Drawer
--	------------------

Media Sizes, Supported	A4 (8.27" x 11.7" or 210mm x 297mm)
	A5 (5.83" x 8.27" or 148mm x 210mm)
	Executive (7.25" x 10.5" or 184mm x 267mm)
	Folio (8.5" x 13" or 216mm x 330mm)
	JIS-B5 (7.17" x 10.12" or 182mm x 257mm)
	Legal (8.5" x 14" or 216mm x 355mm)
	Letter (8.5" x 11" or 216mm x 279mm)
	Statement (5.5" x 8.5" or 140mm x 216mm)
	B5 Envelope (6.93" x 9.84" or 176mm x 250mm)
	C5 Envelope (6.38" x 9.02" or 162mm x 229mm)
	DL Envelope (4.33" x 8.66" or 110mm x 220mm)
	7 3/4 Envelope (3.875" x 7.5" or 98.4mm x 190.5mm)
	9 Envelope (3.875" x 8.9" or 98.4mm x 225.4 mm)
	10 Envelope (4.125" x 9.5" or 105mm x 241mm)
	Universal

Media Types, Supported	Plain Paper
	Transparencies
	Envelopes
	Card Stock
	Paper Labels

Refer to the Card Stock & Label Guide

Paper Input Capacity (Standard)	150 pages 75 gsm bond
--	-----------------------

Paper Input Capacity (Maximum)	400 pages 75 gsm bond
---------------------------------------	-----------------------

Paper Output Capacity (Standard)	100 pages 75 gsm bond
---	-----------------------

Paper Output Capacity (Maximum)	100 pages 75 gsm bond
--	-----------------------

Supplies Yields	Ships with 1,500*-page Starter Return Program Print Cartridge 2,500*-page Print Cartridge *Yield at approximately 5% coverage
------------------------	---

Standard Ports	USB Centronics IEEE 1284 Bidirectional Parallel
-----------------------	--

Optional Local Ports	External Serial Adapter
-----------------------------	-------------------------

Optional Network Ports	External Ethernet 10/100BaseTx External Ethernet 10BaseT/2 External Token-Ring
-------------------------------	--

Network Connectivity	Using an Optional MarkNet Print Server
-----------------------------	--

Additional Products	Local Printing Management and Installation Network Printing
----------------------------	---

Printer Languages (Standard)	PCL 5e Emulation
-------------------------------------	------------------

Font Selection	1 PCL bitmap font 12 scalable PCL fonts 12 scalable PostScript fonts (for Apple Mac only)
-----------------------	---

OCR-A, OCR-B scalable PCL 5e fonts

Bar Code Fonts 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide

Printable Area To within 0.158 in. of the top, bottom, right and left edges

Printable Area (metric) To within 4 mm of the top, bottom, right and left edges

Size (base model), Height 8.7 inches

Size (base model), Width 15.4 inches

Size (base model), Depth 14.2 inches

Size (base model), Height, metric 221 mm

Size (base model), Width, metric 391 mm

Size (base model), Depth, metric 361 mm

Weight (base model) 19.75 lbs.

Weight (base model), metric 8.95 Kg

Noise Level, Idle 30 dBA

Noise Level, Operating 49 dBA

Duty Cycle, Maximum	10,000 pages per month
<hr/>	
Certifications	FCC Class B, UL 60950 3rd Edition, U.S. FDA, IEC 320-1, CSA, ICES Class B, Energy Star
<hr/>	
Warranty	One Year Limited LexExpress Extended Warranty Options Available
<hr/>	
In the Box	Setup Guide Power Cord Online User's Guide Publications CD Laser Printer Drivers, MarkVision and Utilities CD Operator Panel Local Language Overlay Starter Return Program Print Cartridge Quick Reference



**Lexmark T630 Laser
Printer**
10G0100
Powerful workgroup laser printer
at an outstanding value

Tech Specs

Print Technology	Laser, Monochrome
<hr/>	
Print Resolution, Black	1200 Image Quality 1200 x 1200 dpi 300 x 300 dpi 600 x 600 dpi
<hr/>	
Print Speed (letter, black)	Up to 35 pages per minute
<hr/>	
Print Speed (A4, black)	Up to 33 pages per minute

Time to First Page (black)	<8.5 seconds
-----------------------------------	--------------

Processor	300 MHz
------------------	---------

Memory base model, standard	32 MB
------------------------------------	-------

Memory base model, maximum	288 MB
-----------------------------------	--------

Expandable Memory Options	Yes
----------------------------------	-----

Apple Macintosh Operating Systems Supported	Apple Mac OS 8.6 - 9.x Apple Mac OS X
--	--

Microsoft Windows Operating Systems Supported	Microsoft Windows 2000 (Professional/Server/Advanced Server) Microsoft Windows 95 4.00.950 or later Microsoft Windows 98, 2nd edition Microsoft Windows Me Microsoft Windows NT (4.00/4.00 Server) Microsoft Windows XP (Home, Professional)
--	---

Novell Operating Systems Supported	Novell NetWare ^(R) 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support Novell ^(R) Distributed Print Services TM (NDPS TM) 2.0 or later with Lexmark Printing Solution
---	--

Linux Operating Systems Supported	Red Hat Linux 7.2, 7.3, 8.0, 9.0 SuSE 7.3, 8.0, 8.1, 8.2 Linux
--	---

UNIX Operating Systems Supported	Certified Solaris Ready by Sun Microsystems Compaq (Digital) UNIX 4.0D Compaq Tru64 UNIX 4.0F, 5.1 HP-UX 10.20, 11.00 IBM AIX 4.2.1, 4.3.3, 5.1, 5.2 SCO OpenServer 5.0.5, 5.0.6 SGI IRIX 6.5.x Sun Solaris 7, 8, 9 Sun Solaris x86 7, 8, 9 (SCO) UnixWare 2.1.3, 7.1, 7.1.1
---	--

Other Operating Systems Supported	IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform Virtually any platform supporting TCP/IP
--	---

Citrix MetaFrame	Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0 Microsoft Windows NT 4.0 Terminal Server, with Citrix ^(R) MetaFrame ^(R) 1.8 or XP 1.0 Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.
-------------------------	--

Paper Handling Configuration (Standard)	250-Sheet Input Tray 100-Sheet Multipurpose Feeder 250-Sheet Output Bin
--	---

Paper Handling Configuration (Optional)	250-Sheet Drawer 250-Sheet Universally Adjustable Tray with Drawer 400-Sheet Universally Adjustable Tray with Drawer 500-Sheet Drawer 2,000-Sheet Drawer Envelope Feeder 250-Sheet Duplex Unit 1,850-Sheet High-capacity Output Stacker 650-Sheet Output Expander
--	---

Media Sizes, Supported	A4 (8.27" x 11.7" or 210mm x 297mm) A5 (5.83" x 8.27" or 148mm x 210mm) Executive (7.25" x 10.5" or 184mm x 267mm) Folio (8.5" x 13" or 216mm x 330mm) JIS-B5 (7.17" x 10.12" or 182mm x 257mm) Legal (8.5" x 14" or 216mm x 355mm) Letter (8.5" x 11" or 216mm x 279mm) Statement (5.5" x 8.5" or 140mm x 216mm) B5 Envelope (6.93" x 9.84" or 176mm x 250mm) C5 Envelope (6.38" x 9.02" or 162mm x 229mm) DL Envelope (4.33" x 8.66" or 110mm x 220mm) 7 3/4 Envelope (3.875" x 7.5" or 98.4mm x 190.5mm) 9 Envelope (3.875" x 8.9" or 98.4mm x 225.4 mm) 10 Envelope (4.125" x 9.5" or 105mm x 241mm) Universal
-------------------------------	--

Media Types, Supported	Plain Paper Transparencies Envelopes Card Stock Dual Web Labels Integrated Labels Paper Labels Polyester Labels Vinyl Labels
-------------------------------	--

Paper Input Capacity (Standard)	350 pages 75 gsm bond
--	-----------------------

Paper Input Capacity (Maximum)	3850 pages 75 gsm bond
---------------------------------------	------------------------

Paper Output Capacity (Standard)	250 pages 75 gsm bond
---	-----------------------

Paper Output Capacity (Maximum)	2750 pages 75 gsm bond
--	------------------------

Envelope Capacity	85
--------------------------	----

Supplies Yields	Ships with 21,000*-page High Yield Return Program Print Cartridge 5,000*-page Print Cartridge 21,000*-page High Yield Print Cartridge *Yield at approximately 5% coverage
------------------------	--

Standard Ports	USB Centronics IEEE 1284 Bidirectional Parallel One Internal Card Slot
-----------------------	--

Optional Local Ports	External Serial Adapter Internal 1284-B Bidirectional Parallel Internal RS-232C serial
-----------------------------	--

Optional Network Ports	Internal Ethernet 10/100BaseTx Internal Fiber 10Basefl Internal Fiber 100Basefx Internal Token-Ring External Ethernet 10/100BaseTx External Ethernet 10BaseT/2 External Token-Ring Coax/Twinax Adapter for SCS
-------------------------------	---

Network Connectivity	Using an Optional MarkNet Print Server
-----------------------------	--

Bar Code Printing
Custom Business Forms
IBM Mainframe and AS/400 Printing
Internet Printing

Additional Products	Local Printing Management and Installation Network Printing SAP Printing
Printer Languages (Standard)	PCL 6 Emulation PDF V1.2, 1.3 Personal Printer Data Stream (PPDS) PostScript 3 Emulation
Font Selection	158 scalable PostScript fonts 84 scalable PCL fonts 2 PCL bitmap fonts 39 scalable PPDS fonts 5 PPDS bitmap fonts OCR-A, OCR-B scalable PCL 5e fonts
Bar Code Fonts	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
Printable Area	To within 0.167 in. of the top, bottom, right and left edges
Printable Area (metric)	To within 4.2 mm of the top, bottom, right and left edges
Size (base model), Height	13.6 inches
Size (base model), Width	16.6 inches
Size (base model), Depth	19.6 inches
Size (base model), Height, metric	345 mm
Size (base model), Width, metric	421 mm
Size (base model), Depth, metric	498 mm

Weight (base model)	38 lbs.
<hr/>	
Weight (base model), metric	17 Kg
<hr/>	
Noise Level, Idle	31 dBA
<hr/>	
Noise Level, Operating	52 dBA
<hr/>	
Duty Cycle, Maximum	175,000 pages per month
<hr/>	
Certifications	FCC Class B, UL 60950 3rd Edition, U.S. FDA, IEC 320-1, CSA, ICES Class B, Energy Star
<hr/>	
Warranty	One Year Limited LexExpress Extended Warranty Options Available
<hr/>	
In the Box	Laser Printer Power Cord Drivers, MarkVision and Utilities CD Operator Panel Local Language Overlay Quick Reference Setup Guide Online User's Guide Publications CD Return Program High Yield Print Cartridge

**Lexmark W812 Laser Printer**

14K0100

Fast and affordable printer for A3 applications

Tech Specs

Print Technology	Laser, Monochrome
-------------------------	-------------------

Print Resolution, Black	1200 Image Quality 300 x 300 dpi 600 x 600 dpi
--------------------------------	--

Print Speed (letter, black)	Up to 26 pages per minute
------------------------------------	---------------------------

Print Speed (letter, black) Duplex	Up to 19 page sides per minute
---	--------------------------------

Print Speed (A4, black)	Up to 26 pages per minute
--------------------------------	---------------------------

Print Speed (A4, black) Duplex	Up to 19 page sides per minute
---------------------------------------	--------------------------------

Time to First Page (black)	8 seconds
-----------------------------------	-----------

Processor	300 MHz
------------------	---------

Memory base model, standard	16 MB
------------------------------------	-------

Memory base model, maximum	272 MB
-----------------------------------	--------

Expandable Memory Options	Yes
----------------------------------	-----

Apple Macintosh Operating Systems Supported	Apple Mac OS 8.6 - 9.x Apple Mac OS X
--	--

Microsoft Windows Operating Systems Supported	Microsoft Windows 2000 (Professional/Server/Advanced Server) Microsoft Windows 95 4.00.950 or later Microsoft Windows 98, 2nd edition Microsoft Windows Me Microsoft Windows NT (4.00/4.00 Server) Microsoft Windows XP (Home, Professional)
--	---

Novell Operating Systems Supported	Novell NetWare ^(R) 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support Novell ^(R) Distributed Print Services TM (NDPS TM) 2.0 or later with Lexmark Printing Solution
Linux Operating Systems Supported	Caldera eDesktop 2.4 Red Hat Linux 7.2, 7.3, 8.0, 9.0 SuSE 7.3, 8.0, 8.1, 8.2 Linux TurboLinux Workstation 6.0, 6.1
UNIX Operating Systems Supported	Certified Solaris Ready by Sun Microsystems Compaq (Digital) UNIX 4.0D Compaq Tru64 UNIX 4.0F, 5.1 HP-UX 10.20, 11.00 IBM AIX 4.2.1, 4.3.3, 5.1, 5.2 SCO OpenServer 5.0.5, 5.0.6 SGI IRIX 6.5.x Sun Solaris 7, 8, 9 Sun Solaris x86 7, 8, 9 (SCO) UnixWare 2.1.3, 7.1, 7.1.1
Other Operating Systems Supported	IBM iSeries or IBM AS/400 [®] Systems with TCP/IP with OS/400 [®] V3R1 or later using OS/400 Host Print Transform Virtually any platform supporting TCP/IP
Citrix MetaFrame	Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0 Microsoft Windows NT 4.0 Terminal Server, with Citrix ^(R) MetaFrame ^(R) 1.8 or XP 1.0
Paper Handling Configuration (Standard)	250-Sheet Input Tray 150-Sheet Multipurpose Feeder 250-Sheet Output Bin
Paper Handling Configuration (Optional)	250-Sheet Drawer 500-Sheet Drawer Duplex Unit
Media Sizes, Supported	A3 (11.69" x 16.54" or 297mm x 420mm) A4 (8.27" x 11.7" or 210mm x 297mm) A5 (5.83" x 8.27" or 148mm x 210mm) Executive (7.25" x 10.5" or 184mm x 267mm) Folio (8.5" x 13" or 216mm x 330mm) JIS-B4 (10.12" x 14.33" or 257mm x 364mm) JIS-B5 (7.17" x 10.12" or 182mm x 257mm) Ledger (11" x 17" or 279mm x 432mm) Legal (8.5" x 14" or 216mm x 355mm) Letter (8.5" x 11" or 216mm x 279mm)

	Statement (5.5" x 8.5" or 140mm x 216mm) B5 Envelope (6.93" x 9.84" or 176mm x 250mm) C5 Envelope (6.38" x 9.02" or 162mm x 229mm) DL Envelope (4.33" x 8.66" or 110mm x 220mm) 7 3/4 Envelope (3.875" x 7.5" or 98.4mm x 190.5mm) 9 Envelope (3.875" x 8.9" or 98.4mm x 225.4 mm) 10 Envelope (4.125" x 9.5" or 105mm x 241mm) Universal
Media Types, Supported	Plain Paper Transparencies Envelopes Card Stock Paper Labels
Paper Input Capacity (Standard)	400 pages 75 gsm bond
Paper Input Capacity (Maximum)	1400 pages 75 gsm bond
Paper Output Capacity (Standard)	250 pages 75 gsm bond
Paper Output Capacity (Maximum)	250 pages 75 gsm bond
Envelope Capacity	10
Supplies Yields	Ships with 6,000*-page Starter Print Cartridge 12,000*-page Print Cartridge *Yield at approximately 5% coverage
Standard Ports	USB Centronics IEEE 1284 Bidirectional Parallel One Internal Card Slot
Optional Local Ports	External Serial Adapter Internal 1284-C Bidirectional Parallel Internal RS-232C serial
	Internal Ethernet 10/100BaseTx Internal Ethernet 10BaseT/2 Internal Fiber 100Basefx Internal Token-Ring

Optional Network Ports	External 802.11b Wireless External Ethernet 10/100BaseTx External Ethernet 10BaseT/2 External Token-Ring Coax/Twinax Adapter for SCS
Network Connectivity	Using an Optional MarkNet Print Server
Additional Products	Bar Code Printing Custom Business Forms IBM Mainframe and AS/400 Printing Internet Printing Local Printing Management and Installation Local Printing Network Printing SAP Printing
Printer Languages (Standard)	PCL 6 Emulation Personal Printer Data Stream (PPDS) with Euro Support PostScript 3 Emulation
Font Selection	156 scalable PostScript fonts 84 scalable PCL fonts 39 scalable PPDS fonts 2 PCL bitmapped fonts, 5 PPDS bitmapped fonts Chinese and Japanese Font DIMMs Fonts and Symbols Sets for Lexmark T52x, T62x, W812 and W820
Bar Code Fonts	To within 0.16 inches of the top, bottom, right and left edges
Printable Area (metric)	To within 4.0 mm of the top, bottom, right and left edges
Size (base model), Height	12.2 inches
Size (base model), Width	18.1 inches
Size (base model), Depth	16.9 inches

Size (base model), Height, metric	310 mm
Size (base model), Width, metric	459 mm
Size (base model), Depth, metric	430 mm
Weight (base model)	46.5 lbs.
Weight (base model), metric	21 Kg
Noise Level, Idle	28 dBA
Noise Level, Operating	51 dBA
Duty Cycle, Maximum	65,000 pages per month
Warranty	One Year Limited LexExpress
In the Box	Power Cord Clearing Jams Card Publications CD Drivers, MarkVision and Utilities CD Operator Panel Local Language Overlay Quick Reference Card Setup Guide Starter Print Cartridge Laser Printer



Lexmark X215 MFP

18S0100

Want a smart deal on a smart printer. The X215 prints, copies, faxes, and scans all at a business pace. That's smart for your office, ask your re-seller about special



pricing that's smart for your wallet.

Affordable multifunction laser printer for small office and desktop

Tech Specs

Function	Copying
	Faxing
	Printing
	Color Scanning
<hr/>	
Print Resolution, Black	600 x 600 dpi 300 x 300 dpi
<hr/>	
Print Speed (A4, black)	Up to 16 pages per minute
<hr/>	
Print Speed (letter, black)	Up to 17 pages per minute
<hr/>	
Time to First Page (black)	12 seconds
<hr/>	
Copy Speed (letter, black)	Up to 17 pages per minute
<hr/>	
Copy Speed (A4, black)	Up to 16 pages per minute
<hr/>	
First Copy Out Time (mono)	11 Seconds
<hr/>	
Scan Resolution, Enhanced	Up to 4800 x 4800 dpi
<hr/>	
Scan Resolution, Optical	600 x 600 dpi
<hr/>	
Processor	66 MHz

Expandable Memory OptionsNo

Memory MFP, standard16 MB

Fax Modem Speed33.6 Kbps

Scan Area, Maximum8.5 x 14 inches

Scan Area, Maximum (metric)216 x 355 mm

ADF Original Input CapacityUp to 30 pages 75 gsm bond

ADF Maximum Media Weight28 lbs.

**ADF Maximum Media Weight,
metric**90 gsm

Reduce/Enlarge Range25 to 400 %

Document Scanning & DistributionUse PaperPort SE

Standard PortsUSB
Bidirectional Parallel

Optional Network PortsExternal Ethernet 10/100BaseTx

**Paper Handling Configuration
(Standard)**250-Sheet Input Tray
150-Sheet Output Bin
Single Sheet Exit
Single Sheet Manual Feed Slot

Paper Input Capacity (Standard)	250 pages 75 gsm bond
<hr/>	
Paper Output Capacity (Standard)	150 pages 75 gsm bond
<hr/>	
Media Sizes, Supported	A4 (8.27" x 11.7" or 210mm x 297mm) A5 (5.83" x 8.27" or 148mm x 210mm) A6 (4.14" x 5.83" or 105mm x 148mm) Executive (7.25" x 10.5" or 184mm x 267mm) JIS-B5 (7.17" x 10.12" or 182mm x 257mm) Legal (8.5" x 14" or 216mm x 355mm) Letter (8.5" x 11" or 216mm x 279mm) 10 Envelope (4.125" x 9.5" or 105mm x 241mm) 7 3/4 Envelope (3.875" x 7.5" or 98.4mm x 190.5mm) C5 Envelope (6.38" x 9.02" or 162mm x 229mm) C6 Envelope (4.49" x 6.38" or 114mm x 162mm) DL Envelope (4.33" x 8.66" or 110mm x 220mm) Universal
<hr/>	
Media Types, Supported	Card Stock Envelopes Paper Labels Plain Paper Transparencies Refer to the Card Stock & Label Guide
<hr/>	
Microsoft Windows Operating Systems Supported	Microsoft Windows 2000 (Professional/Server/Advanced Server) Microsoft Windows 95 4.00.950 or later Microsoft Windows 98, 2nd edition Microsoft Windows Me Microsoft Windows NT (4.00/4.00 Server) Microsoft Windows XP (Home, Professional)
<hr/>	
Supplies Yields	Ships with 2,000* page Starter Print Cartridge 3,200* page Print Cartridge *Yield at approximately 5% coverage
<hr/>	
Printer Languages (Standard)	Host-Based Printing
<hr/>	
Font Selection	All system fonts supported by the host Operating System
<hr/>	
Size (base model), Height	17 inches
<hr/>	

Size (base model), Width	18.5 inches
---------------------------------	-------------

Size (base model), Depth	16.5 inches
---------------------------------	-------------

Size (base model), Height, metric	432 mm
--	--------

Size (base model), Width, metric	470 mm
---	--------

Size (base model), Depth, metric	419 mm
---	--------

Size, Height	21
---------------------	----

Size (packaged), Width	22 inches
-------------------------------	-----------

Size (packaged), Depth	20 inches
-------------------------------	-----------

Size, Height, Metric	526 mm
-----------------------------	--------

Size, Width, metric	558 mm
----------------------------	--------

Size, Depth, Metric	508 mm
----------------------------	--------

Weight (base model)	30 lbs.
----------------------------	---------

Weight (base model), metric	13.6 Kg
------------------------------------	---------

Weight (packaged)	37.5 lbs.
--------------------------	-----------

Weight (packaged), metric	17 Kg
----------------------------------	-------

Noise Level, Idle	29 dBA
--------------------------	--------

Copy Noise Level, Operating	59 dBA
------------------------------------	--------

Print Noise Level, Operating	53 dBA
-------------------------------------	--------

Scan Noise Level, Operating	55 dBA
------------------------------------	--------

Engine Duty Cycle, Maximum	10,000 pages per month
-----------------------------------	------------------------

Scanner Duty Cycle, Maximum	1,000 pages per month
------------------------------------	-----------------------

Certifications	FCC Class B, DoC, UL 60950 3rd Edition, IEC 320-1, U.S. FDA, CSA, ICES Class B, CS03, ACA TS001, AS/NZS 3260, ACA A-tick mark Class B, CCC Class B
-----------------------	--

Scanner Warranty	LexExpressSM
-------------------------	--------------

Printer Warranty	LexExpressSM
-------------------------	--------------

In the Box	Drivers CD with User's Guide Utilities CD with PaperPort SE RJ-11 Telephone Cable Setup Sheet Starter Print Cartridge Laser MFP RJ-11 Adapter where applicable Operator Panel Local Language Overlay Power Cord
-------------------	---